







PRODUCT SELECTION GUIDE	~v3	mid oper	ation ations	stion the	ad bot of	ion discourse	inuas po	Wester On	ر رين	inscreen Livi	pel opiion	waith width	Najore de a
Automatic lock arm	1			1	1	1	1	1	1		4200	2700	6.5m <sup>2</sup>
Convertible	1		1	1	1	1	1	1	1		3900	2400	9.0m <sup>2</sup>
Florentine	1			1	1	1	1	1	1		3900	2400	9.0m²
Casement	1		1	1	1	1	1	1	1		3900	2400	9.0m <sup>2</sup>
Gear op	1	1	1	1	1	1	1	1	1		5500	2400	16.8m <sup>2</sup>
Channel stop	✓			1	1	1	1		1		3600 -4200	2400 -3000	4-6.5m²
Shopfront	1				1	1	1	1	1		6000	1800	10.8m <sup>2</sup>
Convertible straight drop	1			1	1	1	1	1	1	1	3900	2700	9.0m <sup>2</sup>
Batten straight drop	1				1	1	1	1	1	1	6000	3600	18.0m <sup>2</sup>
Folding arm	1	1	1	1	1		1		1		16000	3500	56.0m <sup>2</sup>
Café	1				1	1	1	1			6000	1500	9.0m <sup>2</sup>
Canopy	1				1	1	1	1			6000	1500	9.0m <sup>2</sup>
Flexi fit pivot arm	1	1	1	<b>√</b> †	1	1	1	1	1		3900	2400	9.0m <sup>2</sup>
Flexi fit auto lock arm	1			<b>√</b> †	1	1	1	1	1		4200	2700	6.5m <sup>2</sup>
Channel X	1	1		1	1	1	1	1	1		3000	3000	9m²
Gear op wire guide / straight drop	✓	1		1	1	1	1	1	1		5500	3600	16.8m²


† standard feature

straight drop



THINKING BLINDS... THINK APOLLO















**AWNINGS** 

TO CONTACT US CALL 132 899 VISIT apollo.net.au OR EMAIL sales@apollo.net.au

#### SHOWROOMS

Brisbane Unit 1, 48 Kingston Road, Underwood QLD 4119 Canberra Unit 1, 6 Wiluna Street, Fyshwick ACT 2609

Coffs Harbour Cnr Isles & Industrial Drives, Coffs Harbour NSW 2450

Newcastle 414 Pacific Highway, Belmont NSW 2280 Port Macquarie Cnr Lake & Blackbutt Roads, Port Macquarie NSW 2444

# FACTORY & SHOWROOM

**Sydney** 172 Silverwater Rd, (Corner Holker St) Silverwater NSW 2128

# ALSO SERVICING

Gold Coast, Sunshine Coast and Regional New South Wales with agents based in Albury, Griffith, Northern Rivers, Orange and the Central West, South Coast & Southern Highlands, Tamworth and Wagga Wagga.

The information and products in this brochure are correct as at 1st August 2012 but may vary after this date. Not all products may be available at all outlets. \*Some conditions appy.















Keeping the sun from beating down on your windows in summer not only reduces the heat inside but also helps save you money on cooling costs.

Apollo's range of durable Awnings can handle the elements and our extensive range of designer colours and patterns add a whole new dimension to your outdoor aesthetics. Your can choose from canvas, acrylics, polyester, screen fabrics, PVC and Colourbond steel.

With five different styles, Apollo has an Awning to suit almost every application.





#### **PIVOT ARM AWNINGS**

**Convertible Awning:** This is the most popular type of Awning due to its versatility. It is suitable for both ground floor and upper level applications and can be operated externally with rope, tape or a winch or internally with tape or a winch. Optional hoods are available in 16 colours, to protect the fabric on the roller when retracted. Apollo's Convertible Awning uses a 5 sided bottom rail, which is available in 12 colours, with spring loaded arms for better Awning stability.

**Florentine Awning:** This is based on the Convertible Awning. It has guide rails connected flush to the wall. Pivot arms can be slid up and down the rails once the Awning is out, to allow more clearance under the awning. This is ideal for doorways and balconies.

Casement Awning: The Casement Awning is also based on the Convertible Style Awning with double arm system. The first set of arms is stopped by a chain attached to the wall allowing height necessary for casement window to open outward. The second set of arms then extend the Awning down past the window.

Flexi Fit Pivot Arm Awning: This is a very versatile Awning that can be operated either internally or externally and is suitable for lower and upper levels. It can be operated either by rope, tape cord lock, crank and motorised options. The Flexi Fit System allows the fabric to protrude past the end fixing points, making it suitable for fibro and cladded homes where fixing points are limited. The Flexi Fit pivot arm system is also available in slide rail and double arm option.

**Gear Operated:** This is a heavy duty Awning suitable for high wind areas and wide window applications, spanning widths up to 5500mm and area coverage of 16.8 square metres. Available in motorised option, which can be coupled with sun and wind sensor for optimum control.

### **SPRING OPERATED AWNINGS**

Automatic Lock Arm Awning: This Awning has a spring loaded top roller and guide rails fitted flush to the wall with standout arms. The Awning is adjusted by guiding the arms up and down the rails. It will automatically lock in when the arms are released in a 90 degree position. This Awning is operated by hand from outside, resists high winds and ideal for ground floor applications, narrow walkways and situations that require the Awning to be as close to the window as possible. Arm sizes from 150mm standouts through to 600mm (increments of 150mm).

Flexi Fit Automatic Lock Arm: Similar to standard automatic lock arms but with aluminium components, 3 sided headbox which allows mounting brackets to be positioned anywhere along the width (instead of at the end of the Awning) the arms can also be positioned on the bottom rail where required. This allows the Awnings to be installed on cladded and fibro walls without the use of unsightly bracing.



Automatic lock arm awning

#### **STRAIGHT DROP AWNINGS:**

**Channel Stop:** This Awning uses a spring operated top roller and side channels which guide the Awning in the drop. It glides freely up and down and may be locked in various positions. Channels are available in white, black, primrose and mill (can be powder coated). This Awning is ideal for verandahs and decks.

**Channel X:** Channel X uses side channels to hold and guide the fabric and is available with an optional hood. The Channel X Awning system can be configured to suit most budgets adding both value to the property and functionality to your outdoor area. Channel X Awnings are available in a wide range of contemporary screen fabrics, clear or tinted PVC, or texstyle acrylic shade fabrics and can be motorised or operated manually with a gear box and crank handle.

**Shop Front Awning:** This Awning is used with J hooks hung from shop awning and is raised and lowered manually with rope. The J hooks hold the Awning in place when it is in down position. It is ideal for providing shade to shop front windows, usually covering the total width of the shop front. Company logos or product details can be sign written to Awnings making the shop more noticeable from the street.



Internally controlled convertible pivot arm awning

**Convertible Straight Drop:** This Awning uses a top roller and is operated via a rope and spool that raises and lowers the Awning. This basic system will cover maximum widths of 3900mm with maximum drop of 2700mm.

**Gear Operated Straight Drop:** It is recommended for sizes outside the maximum specifications for Convertible Straight Drop. This Awning uses a 63mm top and can span widths up to 5500mm. It also gives you the option of motorising the Awning.

Batten Straight Drop: This Awning uses a timber batten at the top and is operated by rope and pulley around the bottom roller. It rolls from the bottom as it is raised. This system gives better fabric coverage because fabric covers the total width of the Awning, therefore there are smaller gaps on the sides. Multiple Awnings across an area can be linked with zippers making this system ideal of outdoor dining areas. This Awning, because it uses a batten at the top can also be made with a sloping top, allowing total coverage on sloping verandahs.

**Wire Guide Awning:** Stainless Steel tension wire guides allows close fitting Awnings to move up and down on the wire guide.

This Awning system is ideal for widows that require close fitting application and verandahs. Can either be gear operated (ground floor) or motorised for high fitting situations or for your comfort.

### **FIXED AWNINGS**

Café: This is a fixed weather protection Fabric Awning generally used over windows, doorways and shop fronts. Maximum width of 6000mm with a maximum projection of 1500mm (longer projection possible with posts).

**Canopy:** The canopy is a Fixed Awning with an aluminium rib substructure covered in either fabric or PVC and used over widows, doors and shopfronts. Canopies are available in 6 shapes: Rectangular (with 100mm radius cast corners), Dutch Hood



Folding arm awning

(100mm radius corners), Boulevarde (300mm radius corners), Half Round, Elipse and Eliptical. These Awnings are ideal as a decorative Awning, great on southern and northern application for sun protection and can be used for rain protection over windows and doorways. The large surface area of these Awnings makes them suitable for sign writing, which allows business premises to standout from the crowd.

Colourbond Steel Awning: Apollo's Colourbond Steel Fixed Awnings offer a practical and cost effective way of protecting your doors and windows from sun and rain. The Awning is cantilevered from the wall with either arm supports or post and provides optimum solar control (northern and southern application) and weather protection.

- Maximum Width 6000mm
- Maximum projection 1360mm (arm), 2500mm (posts)
- Maximum area 8m²
- Available in 15 colours
- Colours can be mixed in any combination, for example main colour to match wall and a few stripes to match guttering
- Optional closed sides available

# **FOLDING ARM AWNINGS**

The Folding Arm Awning is the perfect sun protection retractable system for large areas such as decks and outdoor entertaining areas. It offers great sun protection over large areas (width up to 16m and projection 3.7m). When not required, the arms retract the fabric back onto the roller and out of the way. Available as standard or as Semi Cassette which conceals the mechanism inside the headbox when retracted. Standard operation is by crank (gear operation) or the Awning can be motorised and linked with optional sun and wind sensors which will extend the Awning when sunny and retract the Awning when wind speed is excessive, giving complete peace of mind.

All Awnings come with a 2 year guarantee on manufacture and materials\*. Some components or materials may carry additional manufacturers warranty\*.

