

Clear and Tinted PVC Performance with Ziptrak®

Achieving optimum skin appearance

The Ziptrak® brand is associated with quality and innovation. With a 15 year history of Australian-made and innovative products, Ziptrak® has become Australia's favourite outdoor blind system. Both household and commercial customers uniquely trust Ziptrak® to provide a robust, attractive and long-lasting product.

The Ziptrak® system is custom-made for every installation, and is compatible with a great variety of clear PVC and Sunscreen mesh products, that are not products provided by Ziptrak Pty Ltd. PVC and Sunscreen Mesh are advanced materials, designed to withstand hard Australian conditions with extreme temperature fluctuations. Each Ziptrak® system has a variety of factors that influence the appearance of the blind material, including, but not limited to:

- The size of the opening
- Product selections
- Installation
- Wind and weather variance
- User operation method

Ziptrak® provides effortless and fast operation, whilst securing the blind within a track and can easily be left at any height. As clear and tinted PVC are flexible products by nature, users should not expect these materials to look like a fixed panel surface. Any interior or exterior blind material will naturally have imperfections in the finish. Importantly, customers should note:

- Due to the method in which the PVC skin rolls onto the Top Tube, minor distortion in the PVC can occur vertically near the side Ziptrak® Spline. This distortion is standard and should be expected in most applications, however over time and with the warmth of sunlight, they should reduce or disappear.
- Users may notice the blind seems "baggy" or has a "smiley face" when the bottom bar is left at the half way position (blind is half open). This occurs due to the way the material rolls onto the Top Tube, and is to be expected. To minimize this effect, users are advised to fully retract the blind, and then pull down to the half way position. When the blind is down and locked, users should enjoy a practically wrinkle-free appearance.
- Users should allow a few days for new blinds to "settle", as the PVC has been rolled up prior to installation. Over time, with varying weather conditions, most material distortions should minimize or disappear entirely.

Should you have any questions or concerns about the appearance of your Ziptrak® system, please seek the support of your reseller, or contact Ziptrak® directly.